

NORTH DISTRICT
Rick Fosnow – County Commissioner
776 NE 901 RD
Calhoun, Missouri 65323
Cell: (660) 525-6395

JIM STONE, Presiding Commissioner
448 SE 500 Rd.
Clinton, Missouri 64735
Cell: (660) 351-1133

SOUTH DISTRICT
Dale Lawler – County Commissioner
697 SE 100 RD
Clinton, Missouri 64735
Cell: (660) 525-4649



HENRY COUNTY COMMISSION

Phone (660) 885-7200 / 7201 / 7202



100 W. Franklin

Clinton, Missouri 64735-2080

GUIDELINES FOR NEW ROAD CONSTRUCTION

The physical construction of all new roads in Henry County shall be as follows:

1. The recommended dimensions on all roads shall be:

Right-of-way width	50 feet minimum – no obstructions
Roadway surface width	24 feet minimum
Crown	8"-12" center elevation
Turn arounds	100 feet minimum diameter
Culvert pipe	18 inch minimum for crossroads 12 inch minimum for entrances


2. All brush shall be removed from road right-of-way.
3. The ditches shall be cleared of all weeds and grass. Ditches shall provide adequate drainage. Depth and slope shall be approved by the County Commission.
4. Culverts shall be installed at all intersections and drive entrances. Culvert pipe material shall be new concrete or corrugated metal, and shall be sized according to the areas they are draining.
5. The roadway is to be surfaced with a minimal of 4" aggregate base rock, then the surfacing material shall be equal to the same standards as the township then utilizes for existing County road surfacing in the township in which the new road is being constructed.
6. The project will have 500 tons per mile of rock applied.
7. Rock used shall be 1" or 1 ½" state inspected rock.
8. The County Commission may alter these specifications, if the physical terrain or contour of the ground merits such.

These guidelines are in effect as of June 16, 2009.

HENRY COUNTY COMMISSION



Jim Stone
Presiding Commissioner



Rick Fosnow
North District Commissioner



Dale Lawler
South District Commissioner